LEISTUNG energie

Model: M1250E5

Powered by MTU





Generator Specification

Service	PRP(1)	ESP(2)
Power (kVA)	1125	1250
Power (kW)	900	1000
Rated speed (r.p.m)	1500	
Standard voltage (V)	400/230 V	
Rated at power factor(cos phi)	0.8	

AGG Power gensets are compliant with ISO 9001 and CE standard, which include the following directives:

- 2006/42/EC Machinery safety.
- 2006/95/EC Low voltage
- EN 60204-1: 2006+A1: 2009, EN ISO 12100: 2010, EN ISO 13849-1: 2008, EN 12601 : 2010

(1) PRP (Prime Power):

According to ISO8528-1, prime power is the maximum power available during a variable power sequence, which may be run for an unlimited number of hours per year, between stated maintenance intervals. The permissible average power output during at 24 hours period shall not exceed 80% of the prime power. 10% overload available for governing purposes only.

(2) ESP (Standby Power):


According to ISO 8528-1, It is defined as the maximum power available, under the agreed operating conditions, for which the generating set is capable of delivering for up to 500 hours of operation per year (of which no more than 300 hours for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. No overload capability is available.

Powers	ESP		PRP		Standby
Voltage (V)	KVA	KW	KVA	KW	Amps
415/240	1250	1000	1125	900	1739.1
400/230	1250	1000	1125	900	1804.3
380/220	1250	1000	1125	900	1899.2

Performance Data		
Model		M1250E5
Engine brand		MTU
Engine model		18V2000G65
Speed control type		ADEC
Phase		3
Control system		Digital
Starter motor voltage		24 V
Frequency		50 HZ
Engine speed (RPM)		1500
Fuel Consumption (L/H)	100% standby power	290.97
	100% prime power	264.52
	75% prime power	196.43
	50% prime power	133.57

Standard reference Conditions

Note: Standard reference condition 25°C[77°F] air inlet temp, 100m(328ft) A.S.L 30% relative humidity. Fuel consumption dat with diesel fuel with specific gravity of 0.85 and conforming to BS 2869: 1998, Class A2



Dimension and Weight		
Dimension	Open	Silent
Length (L)	4840mm	6058mm
Width (W)	1830mm	2438mm
Height (H)	2165mm	2591mm
Net Weight	-	-
Fuel Tank (L)	-	-

Note: This parameters allows for some acceptable deviations.

LEISTUNG energie

Engine Specification: 18V2000G65

Basic technical data	
Operated method	Four stroke diesel
Combustion system	Direction injection
Bore	130mm
Stroke	150mm
Displacement, total	31.84 L
Number of cylinders	18
Compression ratio	16.0:1
Flywheel housing flange	SAE 0
Number of intercooler	1
Number of Turbocharger	2

Cooling system	
Coolant temperature(at engine outlet to cooking equipment)	95 °C
Coolant temperature after engine, alarm	97 °C
Coolant temperature after engine, shutdown	102 °C
Coolant antifreeze content, max. permissible	50%
Coolant flow rate	40.0 m3/h
Coolant pump: inlet pressure, min	0.4 bar
Coolant pump: inlet pressure, max	1.52 bar
Pressure loss in off-engine cooling system, max. permissible	0.7 bar
Cooling equipment: height above engine max. permissible	15.2 m
Cooling equipment: design pressure	2.2 bar
Recommended coolant	50% anti freeze/50% water.

Combustion air	
Combustion air volume flow	1.25 m3/sec
Intake air depression	15 mbar

Fuel system	
Fuel supply flow, max.	10 l/min
Fuel return flow, max.	4.5 l/min
Fuel temperature differential before/after engine	40 °C
Fuel fine filter (main circuit): particle retention	0.005mm

Starter system	
Starter, rated voltage	24V
Starter, rated requirement max	1600A
Starter, power requirement at firing speed	800A


Exhaust system	
Exhaust volume flow	3.30 m3/sec
Exhaust temperature after turbocharger	555 °C
Exhaust backpressure limite value	85 mbar

Heat dissipation	
Engine coolant dissipation 100% load	470 kw
Charge-air heat dissipation 100% load	225 kw
Radiation and convection heat, engine	50 kw


LEISTUNG energie

Alternator Specification


Alternator	
Number of phase	3
Power factor (Cos Phi)	0.8
Poles	4
Winding Connections (standard)	Star-serie
Terminals	12
Insulation type	H class
Winding Pitch	2/3
IP rating	IP23
Excitation system	Self-excited
Bearing	Single bearing
Coating	Vacuum impregnation
Voltage regulator	A.V.R
Couping	Flexible disc



Emergency voltage curve



Emergency frequency curve



Options

Engine	Alternator	Generator Sets	Fuel System
▪ Water Jacket Pre-heater ▪ Fuel heater	▪ Winding Temp measuring Instrument ▪ Alternator Pre-heater ▪ PMG ▪ Anti-damp and anti-corrosion treatment ▪ Anti-condensation heater ▪ Winding and bearing RTD	▪ Tools with the machine ▪ Extended range fuel tank ▪ Bunded fuel tank	▪ Low fuel level alarm ▪ Automatic fuel feeding system ▪ Fuel T-valves
Canopy	**Lub oil system**	**Cooling System**	**Control Panel**
▪ Rental type Canopy ▪ Trailer	▪ Oil Pre-heater ▪ Oil temp sensor	▪ Front heat protection	▪ Remote control panel ▪ ATS ▪ Synchronizing controller ▪ Adjustable earth leakage relay

LEISTUNG energie

Control Panel

Configuration

- Emergency stop button
- Protection MCB
- Battery charger
- Integrated aviation plug
- ATS connection
- Digital control module

Features

- 3 phase generator set monitoring
- Support of engines equipped with electronic control unit
- Comprehensive diagnostic message
- Automatic or manual start/stop of the gensets
- Push buttons for simple control, lamp test
- Graphic back-lit LCD display
- Parameters adjustable via keyboard or PC
- Mains measurements（50HZ/60HZ）
- Generator measurements（50HZ/60HZ）
- Comprehensive shutdown or warning on fault condition
- 3 phase Generator protections
  - Over-/under voltage
  - Over-/under frequency
  - Current/voltage asymmetry
  - Over current/overload
- 3 phase AMF function
  - Over-/under frequency
  - Over-/under voltage
  - Voltage asymmetry
- Configurable analog inputs
- Battery voltage, engine speed (pick-up) measurement
- Configurable programmable binary inputs and outputs
- Warm-up and cooling functions
- Generator C.B. and Mains C.B. control with feedback and return timer
- RS232 interface
- Modem communication support
- Hours counter
- Sealed to Ip65
- Event log

Benefits

- Less wiring and components
- Integrated solution
- Less engineering and programming
- User friendly set-up and button layout
- Module can be configured to suit individual applications
- PC software for simplified configuration
- Wide range of communication capabilities

Operation conditions

- Operation temp: -20 ℃ to + 70 ℃
- Storage temp: -30 ℃ to + 80 ℃
- Operating humidity: 95% w/o condensation
- Vibration : 5-25Hz, ±1.6mm
  5-100Hz, a=4g
- Shocks: a= 500m/s²

Options

- Ethernet interface (Remote monitoring and control)
- GSM modem/wireless internet (Remote monitoring and control)
- RS232-RS485 Dual port interface
- Synchronizing control panel
- Distribution board with sockets kit and power busbar
- Battery trickle charge ammeter
- Earth leakage protection
- Earth fault protection
- Low fuel level alarm
- Low fuel level shutdown
- High fuel level alarm
- Fuel transfer system control
- Low coolant level shutdown
- High lube oil temp shutdown
- Overload via alarm switch on breaker
- Engine coolant heater controls
- Control panel heater
- Speed adjust switch
- Oil temp displayed on LCD screen
- Additional 8 inputs and outputs

LEISTUNG energie

United Kingdom | Australia | China | Chile | Germany
Hongkong | Indonesia | Malaysia | Russia | Singapore
South Africa | Thailand | Vietnam

info@leistung-energie.com | www.leistung-energie.com

Unit 1804, South Bank Tower, 55 Upper Ground,
London, United Kingdom SE1 9EY

All information in the document is substantially correct a the time of printing but may be subsequently altered by the company.

Distributed by